

SAFETY DATA SHEET

High Solids Abrasion Resistant CTG 23T3-105

Section 1. Identification

GHS product identifier : High Solids Abrasion Resistant CTG 23T3-105
SDS code : 008084

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Industrial use
Uses advised against
Consumer use

Supplier's details

International Paint LLC
1 East Water Street
Waukegan, IL 60085
USA
Tel. 1 847 623 4200
Email: customer.service@akzonobel.com

Akzo Nobel Coatings Ltd.
4-110 Woodbine Downs Blvd.
Etobicoke ON M9W 5S6
Canada
+1 (800) 618-1010

Importer : Akzo Nobel Performance Coatings, S.A. de C.V.
Anillo Periférico #205 Km16.64
Hacienda San José
García, Nuevo Leon, Mexico.
RFC: ANA9510267C4

Emergency telephone number (with hours of operation) : CHEMTREC +1 (800) 424-9300 (Inside the US)
CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

Section 2. Hazards identification


OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 1A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

GHS label elements

Date of issue/Date of revision	: 7/2/2026	Version	: 3
Date of previous issue	: 12/15/2025		1/17

Section 2. Hazards identification



Signal word : Danger

Hazard statements :

- Flammable liquid and vapor.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- May cause cancer.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, sparks and hot surfaces. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national or international regulations.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Ethene, 1,1,2,2-tetrafluoro-, homopolymer	≥10 - ≤25	9002-84-0
titanium dioxide	≥10 - ≤25	13463-67-7
n-butyl acetate	≥10 - ≤25	123-86-4
heptan-2-one	≥10 - ≤20	110-43-0
2-methoxy-1-methylethyl acetate	≤3	108-65-6
Kieselguhr, soda ash flux-calcined	≤3	68855-54-9
Castor oil	≤3	8001-79-4
Zeolites	≤3	1318-02-1
Cristobalite, as respirable part in whole product <10µm	≤0.3	14464-46-1

Date of issue/Date of revision : 7/2/2026

Version : 3

Date of previous issue : 12/15/2025

2/17

Section 3. Composition/information on ingredients

carbon black, respirable powder	≤0.3	1333-86-4
---------------------------------	------	-----------

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
--------------------	--

Section 4. First aid measures

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Ensure spraying away from persons. Avoid inhalation of vapor, spray or mist. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Ethene, 1,1,2,2-tetrafluoro-, homopolymer	None.
titanium dioxide	OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hours. Form: Total dust
	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust
	ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles
n-butyl acetate	NIOSH REL (United States, 10/2020). STEL: 950 mg/m ³ 15 minutes.
	STEL: 200 ppm 15 minutes.
	TWA: 710 mg/m ³ 10 hours.
	TWA: 150 ppm 10 hours.
	OSHA PEL (United States, 5/2018). TWA: 710 mg/m ³ 8 hours.
	TWA: 150 ppm 8 hours.
	OSHA PEL 1989 (United States, 3/1989). STEL: 950 mg/m ³ 15 minutes.
	STEL: 200 ppm 15 minutes.
	TWA: 710 mg/m ³ 8 hours.
	TWA: 150 ppm 8 hours.
	ACGIH TLV (United States, 1/2023). [Butyl acetates] STEL: 150 ppm 15 minutes.
	TWA: 50 ppm 8 hours.
heptan-2-one	ACGIH TLV (United States, 1/2023). TWA: 50 ppm 8 hours.
	TWA: 233 mg/m ³ 8 hours.
	OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hours.
	TWA: 465 mg/m ³ 8 hours.
	NIOSH REL (United States, 10/2020). TWA: 100 ppm 10 hours.
	TWA: 465 mg/m ³ 10 hours.
	OSHA PEL (United States, 5/2018). TWA: 100 ppm 8 hours.
	TWA: 465 mg/m ³ 8 hours.
2-methoxy-1-methylethyl acetate	OARS WEEL (United States, 7/2018). TWA: 50 ppm 8 hours.
Kieselguhr, soda ash flux-calcined	None.
Castor oil	None.

Section 8. Exposure controls/personal protection

Zeolites Cristobalite, as respirable part in whole product <10µm	None. OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO₂+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable dust NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust OSHA PEL 1989 (United States, 3/1989). Notes: as quartz TWA: 0.05 mg/m³, (as quartz) 8 hours. Form: Respirable dust ACGIH TLV (United States, 1/2023). [Silica, crystalline] Notes: Respirable fraction; see Appendix C, paragraph C. TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction
carbon black, respirable powder	ACGIH TLV (United States, 1/2023). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Refers to Appendix A -- Carcinogens. TWA: 3 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen See Appendix C - Supplemental Exposure Limits TWA: 3.5 mg/m³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 3.5 mg/m³ 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Date of issue/Date of revision	: 7/2/2026	Version	: 3
Date of previous issue	: 12/15/2025		7/17

Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Wear a respirator conforming to EN140 with type A/P2 filter or better.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Color** : Gray.
- Odor** : Solvent.
- Odor threshold** : Not available.
- pH** : Not applicable. [DIN EN 1262]
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : 126°C (258.8°F)
- Flash point** : Closed cup: 27°C (80.6°F) [Pensky-Martens]
- Flammability** : Not available.

Section 9. Physical and chemical properties and safety characteristics

Lower and upper explosion limit : Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)

Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-butyl acetate	11.25096	1.5	DIN EN 13016-2			
heptan-2-one	6.88	0.92				
2-methoxy-1-methylethyl acetate	2.7	0.36				

Relative vapor density : Not available.

Relative density : 1.397 [ISO 8130-2/-3]

Solubility(ies) :

Not available.

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
2-methoxy-1-methylethyl acetate	333	631.4	
heptan-2-one	393	739.4	
n-butyl acetate	415	779	EU A.15

Decomposition temperature : Not available.

Viscosity : Kinematic (room temperature): 394 mm²/s (394 cSt) [DIN EN ISO 3219]
Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]

Weight Volatiles : 32.16% (w/w)

Volume Volatiles : 51.52 % (v/v)

Weight Solids : 67.84 % (w/w)

Volume Solids : 48.48 % (v/v)

Regulatory VOC : 3.7 lbs/gal 448 g/l minus water and exempt solvents

VOC Actual : 3.7 lbs/gal 448 g/l

Particle characteristics

Median particle size : Not applicable.

Percentage of particles : 0

**with aerodynamic diameter
≤ 10 µm**

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Section 10. Stability and reactivity

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate heptan-2-one	LD50 Oral	Rat	10768 mg/kg	-
	LD50 Dermal	Rabbit	12600 uL/kg	-
	LD50 Intraperitoneal	Mouse	400 mg/kg	-
	LD50 Intraperitoneal	Rat	800 mg/kg	-
	LD50 Oral	Mouse	730 mg/kg	-
	LD50 Oral	Rat	1670 mg/kg	-
	LD50 Oral	Rat	1600 mg/kg	-
2-methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Intraperitoneal	Mouse	750 mg/kg	-
	LD50 Intraperitoneal	Mouse	>1500 mg/kg	-
	LD50 Oral	Mouse	>5000 mg/kg	-
	LD50 Oral	Rat	8532 mg/kg	-
	LD50 Oral	Rat	9000 mg/kg	-
	LD50 Intraperitoneal	Mouse	0.37 g/kg	-
Castor oil	LD50 Intraperitoneal	Rat	0.85 g/kg	-
	LD50 Intravenous	Mouse	11 g/kg	-
	LD50 Intravenous	Mouse	11 g/kg	-
	LD50 Intravenous	Mouse	4500 mg/kg	-
	LD50 Oral	Rat	10 g/kg	-
	LD50 Oral	Rat	>15400 mg/kg	-
	LD50 Oral	Rat	>15400 mg/kg	-
carbon black, respirable powder	LD50 Oral	Rat	>15400 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
heptan-2-one	Skin - Mild irritant	Rabbit	-	24 hours 14 mg	-
Castor oil	Eyes - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Guinea pig	-	24 hours 100 mg	-
	Skin - Mild irritant	Rat	-	24 hours 100 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 100 mg	-

Sensitization

Not available.

Section 11. Toxicological information

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethene, 1,1,2,2-tetrafluoro-, homopolymer	-	3	-
titanium dioxide	-	2B	-
Kieselguhr, soda ash flux-calcined	-	3	-
Zeolites	-	3	-
Cristobalite, as respirable part in whole product <10µm	-	1	Known to be a human carcinogen.
carbon black, respirable powder	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Ethene, 1,1,2,2-tetrafluoro-, homopolymer	Category 3	-	Respiratory tract irritation
n-butyl acetate	Category 3	-	Narcotic effects
heptan-2-one	Category 3	-	Narcotic effects
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Cristobalite, as respirable part in whole product <10µm	Category 1	inhalation	-

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision	: 7/2/2026	Version : 3
Date of previous issue	: 12/15/2025	11/17

Section 11. Toxicological information

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied heptan-2-one	3522.4 500	N/A N/A	N/A N/A	77.5 11	N/A N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
n-butyl acetate	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
heptan-2-one	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
Zeolites	Acute LC50 62000 µg/l Fresh water	Fish - Danio rerio	96 hours
	Acute LC50 131000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 200000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 200000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
carbon black, respirable powder	Acute EC50 37.563 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 61.547 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
n-butyl acetate	2.3	-	low
heptan-2-one	2.26	-	low
2-methoxy-1-methylethyl acetate	1.2	-	low
Zeolites	-	0.59 to 0.95	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	No.

Additional information

DOT Classification : **Reportable quantity** 29226.6 lbs / 13268.9 kg [2509.1 gal / 9498.1 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

TDG Classification : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

IMDG : **Emergency schedules** F-E, _S-E_
Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

U.S. Federal regulations

TSCA 5(e) substance consent order: No products found.

TSCA 8(a) PAIR: 2-methoxy-1-methylethyl acetate; octamethylcyclotetrasiloxane

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are active or exempted.

Clean Water Act (CWA) 307: polychloro copper phthalocyanine; ethylbenzene; toluene; benzene

Clean Water Act (CWA) 311: n-butyl acetate; xylene; isobutyl acetate; ethylbenzene; toluene; benzene

Clean Air Act Section 602 : Not listed

Class I Substances

Clean Air Act Section 602 : Not listed

Class II Substances

Section 15. Regulatory information

DEA List I Chemicals : Not listed
(Precursor Chemicals)

DEA List II Chemicals : Not listed
(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 1A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Composition/information on ingredients

Name	%	Classification
Ethene, 1,1,2,2-tetrafluoro-, homopolymer	≥10 - ≤25	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
titanium dioxide	≥10 - ≤25	CARCINOGENICITY - Category 2
n-butyl acetate	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
heptan-2-one	≥10 - ≤20	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
2-methoxy-1-methylethyl acetate	≤3	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Cristobalite, as respirable part in whole product <10µm	≤0.3	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
carbon black, respirable powder	≤0.3	CARCINOGENICITY - Category 2

State regulations

Massachusetts : The following components are listed: TITANIUM DIOXIDE; BUTYL ACETATE; METHYL (N-AMYL) KETONE; ALUMINUM OXIDE; DIATOMACEOUS EARTH

New York : The following components are listed: Butyl acetate

New Jersey : The following components are listed: TITANIUM DIOXIDE; n-BUTYL ACETATE; METHYL n-AMYL KETONE; ALUMINUM OXIDE; SILICA, CRISTOBALITE; CARBON BLACK

Pennsylvania : The following components are listed: ETHENE, TETRAFLUORO-, HOMOPOLYMER; TITANIUM OXIDE; ACETIC ACID, BUTYL ESTER; 2-HEPTANONE; ALUMINUM OXIDE; SILICA AMORPHOUS DIATOMACEOUS EARTH (UNCALCINED); SILICA

California Prop. 65

Section 15. Regulatory information

⚠ WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Titanium dioxide, Silica, crystalline, Carbon black, Silica, crystalline, Ethylbenzene and cumene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
titanium dioxide	-	-
Cristobalite, as respirable part in whole product <10µm	-	-
carbon black, respirable powder	-	-
Crystalline Silica, respirable part in whole product, <10µm	-	-
ethylbenzene	Yes.	-
toluene	-	Yes.
cumene	-	-
benzene	Yes.	Yes.

Inventory list

Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: At least one component is not listed.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): At least one component is not listed. Japan inventory (ISHL): Not determined.
New Zealand	: Not determined.
Philippines	: At least one component is not listed.
Republic of Korea	: At least one component is not listed.
Taiwan	: Not determined.
Thailand	: At least one component is not listed.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Procedure used to derive the classification

Date of issue/Date of revision	: 7/2/2026	Version	: 3
Date of previous issue	: 12/15/2025		16/17

Section 16. Other information

Classification	Justification
FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

History

Date of printing	: 7/2/2026
Date of issue/ Date of revision	: 7/2/2026
Date of previous issue	: 12/15/2025
Version	: 3
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws. Any person using this product must determine for themselves, by preliminary tests or otherwise, the suitability of this product for their purposes. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. The application, use and processing of AkzoNobel's products and the products manufactured by Buyer on the basis of AkzoNobel's technical advice are beyond AkzoNobel's control and, therefore, entirely Buyer's own responsibility. AkzoNobel makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

IA_413

SAFETY DATA SHEET

High Solids Abrasion Resistant CTG PC-216

Section 1. Identification

GHS product identifier : High Solids Abrasion Resistant CTG PC-216
SDS code : 007894

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Industrial use
Uses advised against
Consumer use

Supplier's details

International Paint LLC
1 East Water Street
Waukegan, IL 60085
USA
Tel. 1 847 623 4200
Email: customer.service@akzonobel.com

Akzo Nobel Coatings Ltd.
4-110 Woodbine Downs Blvd.
Etobicoke ON M9W 5S6
Canada
+1 (800) 618-1010

Importer : Akzo Nobel Performance Coatings, S.A. de C.V.
Anillo Periférico #205 Km16.64
Hacienda San José
García, Nuevo Leon, Mexico.
RFC: ANA9510267C4

Emergency telephone number (with hours of operation) : CHEMTREC +1 (800) 424-9300 (Inside the US)
CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (inhalation) - Category 4
SKIN SENSITIZATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

GHS label elements

Date of issue/Date of revision : 6/29/2026
Date of previous issue : 6/11/2026

Version : 2.01
1/14

Section 2. Hazards identification

- Hazard pictograms** :  
- Signal word** : Warning
- Hazard statements** : Flammable liquid and vapor.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Precautionary statements

- Prevention** : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, sparks and hot surfaces. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
- Response** : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national or international regulations.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Hexamethylene diisocyanate, oligomers	≥50 - ≤75	28182-81-2
n-butyl acetate	≥25 - ≤50	123-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Section 4. First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.

- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Ensure spraying away from persons. Avoid inhalation of vapor, spray or mist. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Hexamethylene diisocyanate, oligomers n-butyl acetate	None. NIOSH REL (United States, 10/2020). STEL: 950 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 710 mg/m³ 10 hours. TWA: 150 ppm 10 hours. OSHA PEL (United States, 5/2018). TWA: 710 mg/m³ 8 hours. TWA: 150 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). STEL: 950 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes.

Section 8. Exposure controls/personal protection

TWA: 710 mg/m³ 8 hours.
TWA: 150 ppm 8 hours.
ACGIH TLV (United States, 1/2023). [Butyl acetates]
STEL: 150 ppm 15 minutes.
TWA: 50 ppm 8 hours.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Short Term Exposure Long Term Exposure : Air-supplied half mask must be worn.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid.
Color	: Colorless.
Odor	: Solvent.
Odor threshold	: Not available.
pH	: Not applicable. [DIN EN 1262]
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 126°C (258.8°F)
Flash point	: Closed cup: 27°C (80.6°F) [Pensky-Martens]
Flammability	: Not available.
Lower and upper explosion limit	: Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)
Vapor pressure	:

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-butyl acetate	11.25096	1.5	DIN EN 13016-2			
Hexamethylene diisocyanate, oligomers	0.000018	0.0000024	EU A.4			

Relative vapor density	: Not available.
Relative density	: 1.067 [ISO 8130-2/-3]
Solubility(ies)	:
Not available.	
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	:

Ingredient name	°C	°F	Method
n-butyl acetate	415	779	EU A.15

Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 169 mm ² /s (169 cSt) [DIN EN ISO 3219] Kinematic (40°C (104°F)): Not applicable. [DIN EN ISO 3219]
Weight Volatiles	: 27.44% (w/w)
Volume Volatiles	: 33.24 % (v/v)
Weight Solids	: 72.56 % (w/w)
Volume Solids	: 66.76 % (v/v)
Regulatory VOC	: 2.4 lbs/gal 293 g/l minus water and exempt solvents
VOC Actual	: 2.4 lbs/gal 293 g/l

Particle characteristics

Median particle size	: Not applicable.
-----------------------------	-------------------

Section 9. Physical and chemical properties and safety characteristics

Percentage of particles : 0
with aerodynamic diameter
≤ 10 µm

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hexamethylene diisocyanate, oligomers	LC50 Inhalation Dusts and mists	Rat	18500 mg/m ³	1 hours
n-butyl acetate	LD50 Oral	Rat	10768 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hexamethylene diisocyanate, oligomers	Eyes - Moderate irritant	Rabbit	-	100 mg	-
n-butyl acetate	Skin - Moderate irritant	Rabbit	-	500 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Section 11. Toxicological information

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Hexamethylene diisocyanate, oligomers	Category 3	-	Respiratory tract irritation
n-butyl acetate	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Section 11. Toxicological information

Not available.

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	N/A	N/A	N/A	N/A	2.1
Hexamethylene diisocyanate, oligomers	N/A	N/A	N/A	N/A	1.5

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 32 mg/l Marine water Acute LC50 62000 µg/l Fresh water	Crustaceans - Artemia salina Fish - Danio rerio	48 hours 96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Hexamethylene diisocyanate, oligomers	5.54	367.7	low
n-butyl acetate	2.3	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc})	: Not available.
--	------------------

Other adverse effects	: No known significant effects or critical hazards.
------------------------------	---

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	No.

Additional information

DOT Classification : **Reportable quantity** 18223.1 lbs / 8273.3 kg [2048.3 gal / 7753.8 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

TDG Classification : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

IMDG : **Emergency schedules** F-E, _S-E_

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

U.S. Federal regulations

TSCA 5(e) substance consent order: No products found.

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are active or exempted.

Clean Water Act (CWA) 311: n-butyl acetate

Clean Air Act Section 602 : Not listed

Class I Substances

Clean Air Act Section 602 : Not listed

Class II Substances

DEA List I Chemicals : Not listed
(Precursor Chemicals)

DEA List II Chemicals : Not listed
(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (inhalation) - Category 4
SKIN SENSITIZATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Composition/information on ingredients

Name	%	Classification
Hexamethylene diisocyanate, oligomers	≥50 - ≤75	ACUTE TOXICITY (inhalation) - Category 4 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
n-butyl acetate	≥25 - ≤50	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

State regulations

Massachusetts : The following components are listed: BUTYL ACETATE

New York : The following components are listed: Butyl acetate

New Jersey : The following components are listed: n-BUTYL ACETATE

Pennsylvania : The following components are listed: ACETIC ACID, BUTYL ESTER

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Section 15. Regulatory information

Eurasian Economic Union	: Russian Federation inventory: All components are listed or exempted.
Japan	: Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: All components are listed or exempted.
Turkey	: All components are listed or exempted.
United States	: All components are active or exempted.
Viet Nam	: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method

History

Date of printing	: 6/29/2026
Date of issue/ Date of revision	: 6/29/2026
Date of previous issue	: 6/11/2026
Version	: 2.01
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient

Section 16. Other information

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws. Any person using this product must determine for themselves, by preliminary tests or otherwise, the suitability of this product for their purposes. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. The application, use and processing of AkzoNobel's products and the products manufactured by Buyer on the basis of AkzoNobel's technical advice are beyond AkzoNobel's control and, therefore, entirely Buyer's own responsibility. AkzoNobel makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

IA_413