2 4 0 G



1. IDENTIFICATION:

PRODUCT NAME: LUBRI-BOND A AEROSOL HMIS CODES H F R P

PRODUCT CODE: PLBAAEMSDS

PRODUCT USE .: Low Friction Coating

Manufacturer:

EVERLUBE PRODUCTS
100 COOPER CIRCLE
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300

INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800

NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR

DATE PREPARED: 5/4/2021

2. HAZARDS INDENTIFICATION



CLASSIFICATION:

Flammable Aerosol - Category 1
Aspiration Hazard - Category 1
Carcinogenicity - Category 2
Serious Eye Irritation - Category 2
Gas Under Pressure - Compressed gas
Reproductive Toxicity - Category 2
Skin Corrosion/Irritation - Category 2
Specific target organ toxicity, repeated exposure - Category 2
Specific target organ toxicity, single exposure - Category 3

SIGNAL WORD:

DANGER

HAZARDS STATEMENTS:

H222-Extremely flammable aerosol

H280-Contains gas under pressure; may explode if heated

H304-May be fatal if swallowed and enters airways

H315-Causes skin irritation

H319-Causes serious eye irritation

H336-May cause drowsiness or dizziness

H351-Suspected of causing cancer

H361-Suspected of damaging fertility or the unborn child.

H373-May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood.

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking

P211-Do not spray on an open flame or other ignition source.

P251-Pressurized container: Do not pierce or burn, even after use.

P260-Do not breathe dust/fumes/gas/mist/vapors/spray.



SAFETY DATA SHEET

P261-Avoid breathing dust/fumes/gas/mist/vapours/spray. P264-Wash hands thoroughly after handling P271 Use in well-ventilated area P273-Avoid release to the environment P280-Wear protective gloves/eye protection/face protection. P301+P310-If swallowed, immediately call POISON CONTROL P302+P352-If on skin: Wash with plenty of water P304+P340-If inhaled: Remove person to fresh air and keep comfortable for breathing P305-If in eye rinse cautiously with water for several minutes. P308+P313-If exposed or concerned: Get medical advice/attention. P314-Get medical advice/attetnion if you feel unwell. P331-Do NOT induce vomiting P332+PS313-If skin irritation occurs: Get medical advice/attention. P337+P313-If eye irritation persists: Get medical advise/attention. P362+P364-Take off contaminated clothing and wash it before reuse. P403-P233-P410-P412-Store in a well ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F/50°C. P501-Dispose of contents/container in accordance with

local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS	CAS#	% BY WT.
METHYL ETHYL KETONE	78-93-3	75 -80%
ACGIH TLV: 200 ppm		
ACGIH STEL: 300 ppm		
NIOSH REL: TWA 200 ppm		
NIOSH REL: TWA 590 mg/m3		
OSHA PO: TWA 200 ppm		
OSHA PO: TWA 590 mg/m3		
OSHA PO: STEL 300 ppm		
OSHA PO STEL 885 mg/m3		
EC50 ALGAE ?100 mg/l 96 hr		
LD50 ORAL 3400.0 mg/kg (RATS)		
DC50 VAPORS 2000 PPM (RATS)		
LC50 FISH 100 mg/l 96 hr		
EC50 DAPHNIA >100 mg/l 48 hr		
PROPANE	74-98-6	15% - 20%
OSHA PEL 1000 PPM		
NIOSH REL 1000 PPM		
NIOSHJ IDLH 1000 PPM		
ACGIH TLV 1000 PPM		
LC50 RAT 658mg/l Rat		
ETHYL BENZENE	100-41-4	0% - 5%
ACGIH: 20 ppm TWA		
OSHA 100 ppm TWA; 435 mg/m3 TWA		
OSHA 125 ppm STEL; 545 mg/m3 STEL		
NIOSH 100 ppm TWA; 435 mg/m3 TWA		
NIOSH 125 ppm STEL; 545 mg/m3 STEL		
LD50 ORAL: 3500 mg/kg (rat)		
LC50 Inhalation 17.2 mg/l 4h (rat)		
LD50 Dermal 15354 mg/kg (rabbit)		
LC50 FISH: 11.0-18.0 mg/l 96 hr		
EC50 ALGAE 4.6 mg/l 72 hr		
EC50 DAPHNIA 182.5 mg/l 48 hr		
TOLUENE	108-88-3	0% - 5%
OSHA PEL 200.00 PPM-TWA		
OSHA PEL 300.000 PPM-CEILING		



SAFETY DATA SHEET

OSHA VPEL 100.000 PPM-TWA

OSHA VPEL 150.000 PPM-STEL (SKIN)

ACGIH TLV 50.000 PPM-TWA (SKIN)

ACGIH TLV 150.000 PPM-STEL (SKIN)

LD 50 ORAL RAT: 2.6 g/kg

LC 50 INHALATION RAT: 8000 PPM; 4 h

LD 50 DERMAL RABBIT: 12,124 mg/kg

LC50 FISH 7.63 mg/l 96 h

EC50 INVERTEBRATES 8 mg/l 24 h

EC50 ALGAE 10 mg/l 24h

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used. Consult a doctor if irritation persists.

Ingestion:

Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties:

Flash Point Liquid (Degree F): 15.8 F
Flash Point Method None Known
Flash Point Propellant..... -156 F

Explosive Limits:

Upper explosive limit: 11.5 Lower explosive limit: 1.2

Hazardous Combustion Products:

Oxides of Carbon, Aldehydes, Hdrogen Peroxides or their compounds.

Extinguishing Media:

CO2, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Issue warning "Flammable". Isolate the hazard area and restrict access.



Handle as highly flammable liquid.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Prevent the spill or wash from entering sewers or watercourses.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Maintain good personal hygiene. Avoid breathing processing vapors. Avoid prolonged or repeated skin contact. Wash skin with soap and water after handling. Wash contaminated clothing before re-use.

Storage:

Storage of individual cans should be done in an area below 120F, away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantiles, compliance with NFPA 30B (Manufacture and Storage of Aerosol products) is recommneded.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

None known

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

For personal entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere. Make-up air should always be supplied to balance air exhausted.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:





Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas)....: Extremely Flammable Aerosol

Boiling Point: 174 F
Melting/Freezing Point: -122.8 F

VOC..... 727.292 grams/liter

Flash Point Liquid.....: 15.8 F
Flash Point Propellant....: -156 F
Can Pressure....: 108 psig

Solubility in Water: Insoluble

Density.....: 3.01104 lb/gl

Evaporation Rate: Data not available.

Explosive Limits:

PH Not Applicable.

Volatile (% by Weight).....: 98%

Appearance and Odor Gray/Black liquid, organic solvent odor

Odor Threshold: None known Viscosity None known

Partition Coefficient:....: Data not available Decomposition Temperature ...: Data not available

Autoignition temperature....: 760 F

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released: Oxides of Carbon, Aldehydes, Hydrogen Peroxides or their compounds.

Hazardous Polymerization:

Will not occur.

11. Toxicological Information

Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:



None known

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer):
Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program): None known

Reproductive Toxicity:

Product contains chemical(s) suspected of damaging fertility/unborn child

STOT-single exposure:

If inhaled may cause drowsiness or dizziness May cause drowsiness or dizziness

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

May be fatal if swallowed and enters airways

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil

Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. DO NOT INCINERATE - CONTENTS UNDER PRESSURE.

14. Transport Information



SAFETY DATA SHEET

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number:

UN 1950

UN Shipping Name:

Aerosol, Flammable

Transport Hazard Class:

Class 2.1



Packing Group:

Not Applicable

ENVIRONMENTAL HAZARDS:

Marine Pollutant:

None known

Special Precautions for User:

None known

15. Regulatory Information

U.S. Federal Regulations:

TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXEMPT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:

Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

COMPONENT	CAS #	% BY WT.
PROPANE	74-98-6	15% - 20%

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

State Regulations:

California Prop 65:

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.



International Regulations:

WHMIS Classification:

A, B5, D2A, D2B

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

DATE OF PREPARATION: 5/4/2021

KEY/LEGEND:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: International Carriage of Dangerous Goods by Road

RID: International Carriage of Dangerous Goods by Rail

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act

DOT: Department of Transportation

 ${\tt HMIS: Hazardous \ Materials \ Identification \ System}$

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

IDL: Immediately Dangerous to Life

IMDG: International Maritime Dangerous Goods

IMO: International Maritime Organization

LC: Lethal Concentration

LD: Lethal Dose

NIOSH: National Institute for Occupational Safety & Health

OSHA: Occupational Safety & Health Administration

PPM: Parts Per Million

REL: Recommended Exposure Limit

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limits

STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

VOC: Volatile Organic Compounds

WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABLITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL