



LEAK DETECTOR

GAS LEAK DETECTOR

MIL-PRF-25567 TYPE I
NATO NSN 6850-14-422-4259
NATO NSN 6850-14-514-7430

DEFINITION

Detector of gas leakage.

APPLICATIONS

- Piping, taps, connections, water works, pipes, valves.
- Natural gas vehicles feed system.
- Compressed air installations, gas-cylinder pressure gauges, refrigeration installations.
- **LEAK DETECTOR** contains no mineral oils and is suitable for use with all gases, including oxygen.

PRODUCT BENEFITS

- Ecological.
- Biodegradable.
- Effective even for small leaks.
- Non-toxic.
- Non-corrosive.

PHYSICAL PROPERTIES

Aspect	Liquid
Colour	Transparent light yellow
Flash point	None
Boiling point	>100°C
pH	8.5

DIRECTIONS FOR USE

Spray on the area to be examined. Bubbles will form at the site of the leak.

PACKAGING

400 ml aerosol	ref. O 952 A4	x 12
1 L bottle	ref. O 952 J1	x 4
60 L drum	ref. O 952 O5	x 1

LEAK DETECTOR 952 packaged in 5 and 60 litres complies with EIGA / ICG doc78/08/E recommendations:

- Product contains no ammonia.
- No ammonia content reduces the risk of SCC on copper-based alloys.
- Product is water-based; residue has an autoignition temperature of > 100°C.
- Product contains no halides.
- Product is non-corrosive.
- Product does not harm the environment.

See also:

ORAPI 745 - FORMULE GRAND FROID -30°C ref. O 745 J1 in 5 L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.