

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	000000000050603705	Date of first issue: 22.09.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Naftoseal MC-780 B-1/2 Base Compound (162 L)

Product code : 000000000050603705

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Base mass

Recommended restrictions on use : Uses other than recommended

1.3 Details of the supplier of the safety data sheet

Company:
Chemetall Ltd.
Napier House, Auckland Park
MK1 1BU Bletchley, Milton Keynes
Great Britain
+44 1908 649333
sds.global-chemetall@basf.com

Telephone: +44 1908 649333
E-mail address: sds.global-chemetall@basf.com

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard Statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P273 Avoid release to the environment.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic compounds
polymers
inorganic compounds
pigment

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Liquid polysulphide polymer with thiol end groups (MW>1800)	68611-50-7	Aquatic Chronic 3; H412	>= 25 - < 50
Liquid polysulphide polymer with thiol end groups (MW<1800)	68611-50-7	Aquatic Chronic 2; H411	>= 15 - < 20
modified polysulfide polymer	2361542-48-3	Aquatic Chronic 3; H412	>= 12.5 - < 15

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

Substances with a workplace exposure limit :			
Titanium dioxide	13463-67-7 236-675-5 UK-20-2749242067-7-0000 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000		$\geq 15 - < 20$
Limestone	1317-65-3 215-279-6 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000		$\geq 3 - < 5$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- | | |
|-------------------------|---|
| General advice | : Never give anything by mouth to an unconscious person.
Move out of dangerous area.
In all cases of doubt, or when symptoms persist, seek medical attention.
Immediately remove contaminated clothing.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
First aid personnel should pay attention to their own safety. |
| If inhaled | : If breathed in, move person into fresh air.
If breathing is irregular or stopped, administer artificial respiration.
If symptoms persist, call a physician. |
| In case of skin contact | : Do NOT use solvents or thinners.
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If symptoms persist, call a physician. |
| In case of eye contact | : In case of eye contact, remove contact lens and rinse imme- |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

diately with plenty of water, also under the eyelids, for at least 15 minutes.

If symptoms persist, call a physician.

If swallowed

: Rinse mouth.

Do NOT induce vomiting.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.
No known specific antidote.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder
Carbon dioxide (CO₂)
Water spray
Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.
For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.
Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Avoid subsoil penetration.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).
Do not return residues to the storage containers.
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
The workplace should be equipped with an emergency shower and eye-rinsing facility.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Do not breathe vapors or spray mist.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedings.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature : < 26 °C

Packaging material : Suitable material: tinned carbon steel (Tinplate), Carbon steel (Iron), Stainless steel 1.4301 (V2), Polypropylene, Polyethyleneterephthalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Titanium dioxide	13463-67-7	TWA (inhalable)	10 mg/m3	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version 5.0 Revision Date: 21.01.2026 SDS Number: 0000000000506037 Date of last issue: 13.04.2025
Date of first issue: 22.09.2023
05

		dust)		
		TWA (Respirable dust)	4 mg/m3	GB EH40
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. nitrile rubber (NBR) - 0.4 mm coating thickness Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1. The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection

Skin and body protection : Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Filter type : Organic vapor Type (A)

Protective measures : Do not breathe vapour/spray.
Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Color	: gray
Odor	: sulfurous
Odor Threshold	: not determined
pH	: substance/mixture is non-soluble (in water)
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: > 95 °C Method: ISO 3679 No flash point - Measurement made up to the indicated temperature., does not flash
Evaporation rate	: not determined
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapor pressure	: not determined (20 °C) not determined (50 °C)
Relative vapor density	: Heavier than air.
Relative density	: No data available
Density	: 0.8373 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: not determined
Partition coefficient: n-octanol/water	: not applicable for mixtures
Autoignition temperature	: > 200.00 °C
Decomposition temperature	: No decomposition if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

Viscosity		
Viscosity, kinematic	:	not determined (40 °C) not determined (23 °C)
Flow time	:	< 30 s at 23 °C Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids)	:	hardly combustible
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No hazardous reactions when stored and handled according to instructions.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks. Protect from frost. Heat. Avoid direct sunlight.
---------------------	---	--

10.5 Incompatible materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: Not applicable

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

SECTION 14: Transport information

14.1 UN number

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.2 UN proper shipping name

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.4 Packing group

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 72, 3
--	---	---

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
---	---	----------------

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
---	---	----------------

Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
--	---	----------------

UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
--	---	----------------

Control of Major Accident Hazards Regulations 2015 (COMAH)	:	Not applicable
--	---	----------------

Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0.15 %
----------------------------	---	--

Volatile organic compounds (VOC) content: 1.25 g/l
VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of other abbreviations

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Base Compound (162 L)

Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2025
5.0	21.01.2026	0000000000506037 05	Date of first issue: 22.09.2023

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	000000000050603679	Date of first issue: 25.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	Naftoseal MC-780 B-1/2 Hardener (12 L)
Product code	:	000000000050603679
Unique Formula Identifier (UFI)	:	WCGN-F2GU-S009-KG1Q

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	hardener
Recommended restrictions on use	:	Uses other than recommended

1.3 Details of the supplier of the safety data sheet

Company:
Chemetall Ltd.
Napier House, Auckland Park
MK1 1BU Bletchley, Milton Keynes
Great Britain
+44 1908 649333
sds.global-chemetall@basf.com

Telephone: +44 1908 649333
E-mail address: sds.global-chemetall@basf.com

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036	Date of first issue: 25.01.2023
		79	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Danger	
Hazard Statements	:	H302 H315 H317 H319 H372 H412	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Precautionary Statements	:	Prevention: P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P314 Get medical advice/ attention if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical	

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

advice/ attention.

Hazardous ingredients which must be listed on the label:

manganese dioxide
phthalic anhydride

Authorization number : UKREACH/25/14/00

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic compounds
inorganic compounds

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
manganese dioxide	1313-13-9 215-202-6 025-001-00-3 UK-20-2749242067-7-0000 UK-20-9702550300-0-0000	Acute Tox. 4; H302 Acute Tox. 4; H332 STOT RE 1; H372 (Central nervous system)	>= 50 - < 75
sulfur	7704-34-9 231-722-6 016-094-00-1 UK-20-2749242067-7-0000 UK-20-9702550300-0-0000	Skin Irrit. 2; H315	>= 2 - < 2.5
sodium hydroxide	1310-73-2 215-185-5	Met. Corr. 1; H290 Skin Corr. 1A;	>= 0.5 - < 1

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version 6.1 Revision Date: 12.09.2025 SDS Number: 0000000000506036 Date of last issue: 28.08.2025
Date of first issue: 25.01.2023
79

	011-002-00-6 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000	H314 Eye Dam. 1; H318 specific concentration limit Skin Corr. 1A; H314 ≥ 5 % Skin Corr. 1B; H314 2 - < 5 % Skin Irrit. 2; H315 0.5 - < 2 % Eye Irrit. 2; H319 0.5 - < 2 %	
phthalic anhydride	85-44-9 201-607-5 607-009-00-4 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT SE 3; H335 (Respiratory system)	≥ 0.3 - < 0.5
Nonylphenol Ethoxylate	68412-54-4 500-209-1	Acute Tox. 4; H302 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	≥ 0.1 - < 0.2

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036	Date of first issue: 25.01.2023
		79	

Move out of dangerous area.
In all cases of doubt, or when symptoms persist, seek medical attention.
Immediately remove contaminated clothing.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
First aid personnel should pay attention to their own safety.

- | | | |
|-------------------------|---|--|
| If inhaled | : | If breathed in, move person into fresh air.
If breathing is irregular or stopped, administer artificial respiration.
If symptoms persist, call a physician. |
| In case of skin contact | : | Do NOT use solvents or thinners.
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If symptoms persist, call a physician. |
| In case of eye contact | : | If easy to do, remove contact lens, if worn.
Call a physician immediately.
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. |
| If swallowed | : | Rinse mouth with water.
Do not induce vomiting due to aspiration hazard.
Keep at rest.
If swallowed, call a poison control center or doctor immediately. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|---|
| Symptoms | : | Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. |
| Risks | : | Harmful if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Causes damage to organs through prolonged or repeated exposure. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

No known specific antidote.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Cool containers/tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.
For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.
Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Avoid subsoil penetration.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Do not breathe vapors or spray mist.
Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.
Hygiene measures	:	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions	:	Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the
---	---	---

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version 6.1 Revision Date: 12.09.2025 SDS Number: 0000000000506036 Date of last issue: 28.08.2025
Date of first issue: 25.01.2023
79

original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Storage period : 12 Months

Recommended storage temperature : < 26 °C

Packaging material : Suitable material: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethyleneterephthalate (PET), Polypropylene, Carbon steel (Iron), tinned carbon steel (Tinplate)

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
manganese dioxide	1313-13-9	TWA (Inhalable)	0.2 mg/m ³ (Manganese)	GB EH40
		TWA (Respirable fraction)	0.05 mg/m ³ (Manganese)	GB EH40
		TWA (inhalable fraction)	0.2 mg/m ³ (Manganese)	2017/164/EU
	Further information: Indicative			
		TWA (Respirable fraction)	0.05 mg/m ³ (Manganese)	2017/164/EU
	Further information: Indicative			
sodium hydroxide	1310-73-2	STEL	2 mg/m ³	GB EH40
phthalic anhydride	85-44-9	TWA	4 mg/m ³	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL	12 mg/m ³	GB EH40
	Further information: Capable of causing occupational asthma.			

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036	Date of first issue: 25.01.2023
		79	

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)
Hand protection

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. chloroprene rubber (CR) - 0.5 mm coating thickness Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1 The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Preventive skin protection

Skin and body protection : Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Filter type : Organic vapor Type (A)

Protective measures : Do not breathe vapour/spray.
Eye wash fountains and safety showers must be easily accessible.

Persons with a history of allergies, asthma, recurrent or chronic respiratory disease must not be employed in any process in which this product is used. Persons using this product should undergo lung function tests at regular intervals.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Color : brown
Odor : characteristic
Odor Threshold : not determined

pH : substance/mixture is non-soluble (in water)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

Melting point/ range	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	> 99 °C Method: ISO 3679
Evaporation rate	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapor pressure	:	not determined (20 °C) not determined (50 °C)
Relative density	:	No data available
Density	:	1.700 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200.00 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	400,000 mPa.s
Viscosity, kinematic	:	not determined (23 °C) not determined (40 °C)
Flow time	:	< 30 s at 23 °C Cross section: 3 mm Method: ISO 2431
Explosive properties	:	Not explosive

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Does not sustain combustion.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazardous reactions when stored and handled according to instructions.

10.4 Conditions to avoid

Conditions to avoid : Heat.
Avoid direct sunlight.
Protect from frost.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 995.49 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

phthalic anhydride:

Acute oral toxicity : LD50 (Rat): 1,530 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Nonylphenol Ethoxylate:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

phthalic anhydride:

Partition coefficient: n-octanol/water : log Pow: 1.60 (20 °C)
GLP: No information available.
Remarks: Information taken from reference works and the literature.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture contains components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	: Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.2 UN proper shipping name

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN	: Not regulated as a dangerous good
-----	-------------------------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Chemetall
expect more⁺

Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036	Date of first issue: 25.01.2023
		79	

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:
Number on list 46b, 46a., 3

Number on list 46b, 46a.

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Nonylphenol Ethoxylate

The Persistent Organic Pollutants Regulations (retained) : Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036 79	Date of first issue: 25.01.2023

Regulation (EU) 2019/1021 as amended for Great Britain)

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Nonylphenol Ethoxylate

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0.19 %

Volatile organic compounds (VOC) content: 3.23 g/l
VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H290	: May be corrosive to metals.
H302	: Harmful if swallowed.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H372	: Causes damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036	Date of first issue: 25.01.2023
		79	

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Met. Corr.	: Corrosive to Metals
Resp. Sens.	: Respiratory sensitization
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Naftoseal MC-780 B-1/2 Hardener (12 L)

Version	Revision Date:	SDS Number:	Date of last issue: 28.08.2025
6.1	12.09.2025	0000000000506036	Date of first issue: 25.01.2023
		79	

Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT RE 1	H372
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN