

SAFETY DATA SHEET

AERODUR Primer S15/90 Yellow

Section 1. Identification

GHS product identifier : AERODUR Primer S15/90 Yellow

SDS code : A36068

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Industrial use	
Uses advised against	
Consumer use	

Supplier's details

International Paint LLC
1 East Water Street
Waukegan, IL 60085
USA
Tel. 1 847 623 4200
Email: customer.service@akzonobel.com

Akzo Nobel Coatings Ltd.
4-110 Woodbine Downs Blvd.
Etobicoke ON M9W 5S6
Canada
+1 (800) 618-1010

Importer : Akzo Nobel Performance Coatings, S.A. de C.V.
Anillo Periférico #205 Km16.64
Hacienda San José
García, Nuevo Leon, Mexico.
RFC: ANA9510267C4

Emergency telephone number (with hours of operation) : CHEMTREC +1 (800) 424-9300 (Inside the US)
CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
ACUTE TOXICITY (inhalation) - Category 4
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
RESPIRATORY SENSITIZATION - Category 1
SKIN SENSITIZATION - Category 1
GERM CELL MUTAGENICITY - Category 1
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Date of issue/Date of revision

: 10/14/2025

Version : 4

Date of previous issue

: 8/28/2025

1/22

Section 2. Hazards identification

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

- : Highly flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause drowsiness or dizziness.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure. (cerebral nervous system)

Precautionary statements

Prevention

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wear respiratory protection. Keep away from heat, sparks and hot surfaces. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response

- : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage

- : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal

- : Dispose of contents and container in accordance with all local, regional, national or international regulations.

Hazards not otherwise classified

- : None known.

Section 3. Composition/information on ingredients

Substance/mixture

- : Mixture

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
strontium chromate	≥10 - <20	7789-06-2
2-methoxy-1-methylethyl acetate	≥10 - ≤25	108-65-6
Kaolin	≥10 - ≤25	1332-58-7
butanone	≥10 - ≤25	78-93-3
toluene	≥10 - ≤25	108-88-3
isobutyl acetate	≤10	110-19-0
titanium dioxide	≤3	13463-67-7
barium chromate	<1	10294-40-3
propylidynetrimethanol	≤1	77-99-6
Solvent naphtha (petroleum), heavy arom.	≤0.3	64742-94-5
Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines	≤0.3	68647-95-0
crystalline silica, respirable powder	≤0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
wheezing and breathing difficulties
asthma
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Ensure spraying away from persons. Avoid inhalation of vapor, spray or mist. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	6/22

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
strontium chromate	<p>ACGIH TLV (United States, 1/2022). Notes: measured as Cr TWA: 0.0005 mg/m³, (measured as Cr) 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). [Chromic acid and chromates (as CrO₃)]</p> <p>Notes: as CrO₃ CEIL: 0.1 mg/m³, (as CrO₃)</p> <p>OSHA PEL Z2 (United States, 2/2013). [Chromic acid and chromates] CEIL: 1 mg/10m³</p> <p>OSHA PEL (United States, 5/2018). [Chromium (VI) compounds] TWA: 0.005 mg/m³, (as Cr) 8 hours.</p> <p>NIOSH REL (United States, 10/2020). [chromic acid and chromates] TWA: 0.0002 mg/m³, () 8 hours.</p> <p>OARS WEEL (United States, 7/2018). TWA: 50 ppm 8 hours.</p> <p>None.</p>
2-methoxy-1-methylethyl acetate	
Kaolin	
butanone	<p>ACGIH TLV (United States, 1/2022). Notes: Substances for which there is a Biological Exposure Index or Indices</p> <p>STEL: 885 mg/m³ 15 minutes. STEL: 300 ppm 15 minutes. TWA: 590 mg/m³ 8 hours. TWA: 200 ppm 8 hours.</p> <p>NIOSH REL (United States, 10/2020). STEL: 885 mg/m³ 15 minutes. STEL: 300 ppm 15 minutes. TWA: 590 mg/m³ 10 hours. TWA: 200 ppm 10 hours.</p> <p>OSHA PEL (United States, 5/2018). TWA: 590 mg/m³ 8 hours. TWA: 200 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). STEL: 885 mg/m³ 15 minutes. STEL: 300 ppm 15 minutes. TWA: 590 mg/m³ 8 hours. TWA: 200 ppm 8 hours.</p>
toluene	<p>NIOSH REL (United States, 10/2020). STEL: 560 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m³ 10 hours. TWA: 100 ppm 10 hours.</p> <p>OSHA PEL Z2 (United States, 2/2013). AMP: 500 ppm 10 minutes. CEIL: 300 ppm TWA: 200 ppm 8 hours.</p> <p>ACGIH TLV (United States, 1/2022). Ototoxicant. TWA: 20 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). Notes: See Table Z-2.</p>

Section 8. Exposure controls/personal protection

isobutyl acetate	<p>STEL: 560 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m³ 8 hours. TWA: 100 ppm 8 hours.</p> <p>NIOSH REL (United States, 10/2020). TWA: 700 mg/m³ 10 hours. TWA: 150 ppm 10 hours.</p> <p>OSHA PEL (United States, 5/2018). TWA: 700 mg/m³ 8 hours. TWA: 150 ppm 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 700 mg/m³ 8 hours. TWA: 150 ppm 8 hours.</p> <p>ACGIH TLV (United States, 1/2022). [Butyl acetates] STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
titanium dioxide	<p>OSHA PEL (United States, 5/2018). TWA: 15 mg/m³ 8 hours. Form: Total dust</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m³ 8 hours. Form: Total dust</p> <p>ACGIH TLV (United States, 1/2022). TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles</p>
barium chromate	<p>ACGIH TLV (United States, 1/2022). [inorganic chromium VI compounds] TWA: 0.0002 mg/m³, (measured as Cr) 8 hours. Form: Inhalable fraction STEL: 0.0005 mg/m³, (measured as Cr) 15 minutes. Form: Inhalable fraction</p> <p>OSHA PEL Z2 (United States, 2/2013). [Chromic acid and chromates] CEIL: 1 mg/10m³</p> <p>OSHA PEL (United States, 5/2018). [Chromium (VI) compounds] TWA: 0.005 mg/m³, (as Cr) 8 hours.</p> <p>NIOSH REL (United States, 10/2020). [chromic acid and chromates] TWA: 0.0002 mg/m³, () 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). [Chromic acid and chromates (as CrO₃)]</p> <p>Notes: as CrO₃ CEIL: 0.1 mg/m³, (as CrO₃)</p>
propylidynetrimethanol Solvent naphtha (petroleum), heavy arom. Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines crystalline silica, respirable powder	<p>None.</p> <p>None.</p> <p>None.</p> <p>OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO₂+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / (%SiO₂+2) 8 hours. Form: Respirable</p> <p>OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable dust</p> <p>OSHA PEL 1989 (United States, 3/1989).</p>

Section 8. Exposure controls/personal protection

Notes: as quartz

TWA: 0.1 mg/m³, (as quartz) 8 hours. Form: Respirable dust

ACGIH TLV (United States, 1/2022). [Silica, crystalline] Notes: Respirable fraction; see Appendix C, paragraph C.

TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction

NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE] Notes: See Appendix A - NIOSH Potential Occupational Carcinogen

TWA: 0.05 mg/m³ 10 hours. Form: respirable dust

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.
Color : Yellow.
Odor : Typical.
Odor threshold : Not available.
pH : Not applicable. [DIN EN 1262]
Melting point/freezing point : Not available.
Boiling point, initial boiling point, and boiling range : 80°C (176°F)
Flash point : Closed cup: 5°C (41°F) [Pensky-Martens]
Flammability : Not available.
Lower and upper explosion limit : Greatest known range: Lower: 1.8% Upper: 11.5% (butanone)

Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
butanone	78.76	10.5				
toluene	23.17	3.1				
isobutyl acetate	15.75	2.1	DIN EN 13016-2			

Relative vapor density : Not available.

Relative density : 1.293 [ISO 8130-2/3]

Solubility(ies) :
Not available.

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
2-methoxy-1-methylethyl acetate	333	631.4	
butanone	404	759.2	
isobutyl acetate	430	806	EU A.15

Decomposition temperature : Not available.

Section 9. Physical and chemical properties and safety characteristics

Viscosity	:	Kinematic (room temperature): 278 mm ² /s (278 cSt) [DIN EN ISO 3219] Kinematic (40°C (104°F)): 90 mm ² /s (90 cSt) [DIN EN ISO 3219]		
Weight Volatiles	:	41.92% (w/w)		
Volume Volatiles	:	61.79 % (v/v)		
Weight Solids	:	58.08 % (w/w)		
Volume Solids	:	38.21 % (v/v)		
Regulatory VOC	:	4.5	lbs/gal	542 g/l minus water and exempt solvents
VOC Actual	:	4.5	lbs/gal	542 g/l
Particle characteristics				
Median particle size	:	Not applicable.		
Percentage of particles with aerodynamic diameter $\leq 10 \mu\text{m}$:	0		

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
strontium chromate	LC50 Inhalation Dusts and mists LD50 Intratracheal	Rat Rat	0.27 mg/l 16.6 mg/kg	4 hours -
2-methoxy-1-methylethyl acetate	LD50 Oral LD50 Dermal	Rat Rabbit	3118 mg/kg >5 g/kg	- -
butanone	LD50 Intraperitoneal LD50 Intraperitoneal LD50 Oral LD50 Oral LD50 Oral LC50 Inhalation Vapor LC50 Inhalation Vapor LD50 Dermal	Mouse Mouse Mouse Rat Rat Mouse Rat Rabbit	750 mg/kg >1500 mg/kg >5000 mg/kg 8532 mg/kg 9000 mg/kg 32 g/m ³ 23500 mg/m ³ 6480 mg/kg	- - - - - 4 hours 8 hours -

Section 11. Toxicological information

toluene	LD50 Intraperitoneal	Guinea pig	2 g/kg	-
	LD50 Intraperitoneal	Mouse	616 mg/kg	-
	LD50 Intraperitoneal	Rat	607 mg/kg	-
	LD50 Oral	Mouse	3000 mg/kg	-
	LD50 Oral	Rat	2737 mg/kg	-
	LC50 Inhalation Gas.	Mouse	400 ppm	24 hours
	LC50 Inhalation Vapor	Mouse	30000 mg/m ³	2 hours
	LC50 Inhalation Vapor	Mouse	19900 mg/m ³	7 hours
	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Dermal	Rabbit	14100 uL/kg	-
	LD50 Intraperitoneal	Guinea pig	500 mg/kg	-
	LD50 Intraperitoneal	Mouse	59 mg/kg	-
	LD50 Intraperitoneal	Rat	1332 mg/kg	-
	LD50 Intravenous	Rat	1960 mg/kg	-
	LD50 Oral	Rat	636 mg/kg	-
	LD50 Route of exposure unreported	Mouse	2 g/kg	-
	LD50 Route of exposure unreported	Rat	6900 mg/kg	-
isobutyl acetate	LD50 Subcutaneous	Mouse	2250 mg/kg	-
	LD50 Dermal	Rabbit	>17400 mg/kg	-
	LD50 Oral	Rabbit	4763 mg/kg	-
propylidynetrimethanol	LD50 Oral	Rat	13400 mg/kg	-
	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral	Mouse	14000 mg/kg	-
	LD50 Oral	Rat	14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
butanone	Skin - Mild irritant	Rabbit	-	24 hours 14 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 402 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
isobutyl acetate	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-
Solvent naphtha (petroleum), heavy arom.	Eyes - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 UI	-

Sensitization

Not available.

Mutagenicity

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	12/22

Section 11. Toxicological information

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
strontium chromate	+	1	Known to be a human carcinogen.
toluene	-	3	-
titanium dioxide	-	2B	-
barium chromate	+	1	Known to be a human carcinogen.
crystalline silica, respirable powder	-	1	Known to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
strontium chromate	Category 3	-	Respiratory tract irritation
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
butanone	Category 3	-	Narcotic effects
toluene	Category 3	-	Narcotic effects
isobutyl acetate	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
toluene	Category 2	inhalation	cerebral nervous system
barium chromate	Category 1	-	kidneys, respiratory tract
Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines	Category 2	-	-
crystalline silica, respirable powder	Category 1	inhalation	lungs

Aspiration hazard

Name	Result
toluene	ASPIRATION HAZARD - Category 1
Solvent naphtha (petroleum), heavy arom.	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact

: Causes serious eye irritation.

Inhalation

: Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	13/22

Section 11. Toxicological information

Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Inhalation : Adverse symptoms may include the following:
 wheezing and breathing difficulties
 asthma
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Skin contact : Adverse symptoms may include the following:
 irritation
 redness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Ingestion : Adverse symptoms may include the following:
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : May cause genetic defects.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	14/22

Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	2636.6	N/A	N/A	N/A	1.4
strontium chromate	500	N/A	N/A	N/A	0.27
toluene	N/A	N/A	N/A	49	N/A
barium chromate	100	300	N/A	N/A	0.05

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
butanone	Acute EC50 >500 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 >500000 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 5091000 µg/l Fresh water	Daphnia - Daphnia magna - Larvae	48 hours
toluene	Acute LC50 5600 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours
	Acute LC50 3220000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 16500 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6.88 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 6.56 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 19600 µg/l Fresh water	Daphnia - Daphnia magna - Larvae	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute EC50 6780 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 56.3 ppm Marine water	Crustaceans - Americamysis bahia	48 hours
	Acute LC50 15.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 15500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 86.3 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 6410 µg/l Marine water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Acute LC50 5800 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 6780 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours

Section 12. Ecological information

titanium dioxide	Chronic NOEC 2 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
propylidynetrtrimethanol	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
propylidynetrtrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-methoxy-1-methylethyl acetate	1.2	-	low
butanone	0.3	-	low
toluene	2.73	90	low
isobutyl acetate	2.3	-	low
propylidynetrtrimethanol	-0.47	<1	low
Solvent naphtha (petroleum), heavy arom.	2.8 to 6.5	99 to 5780	high

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
butanone	78-93-3	Listed	U159
toluene	108-88-3	Listed	U220

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3  	3 	3  	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.	Marine Pollutant(s): strontium chromate	Yes. The environmentally hazardous substance mark is not required.

Additional information

DOT Classification

: **Reportable quantity** 52.733 lbs / 23.941 kg [4.8913 gal / 18.516 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.

IMDG

: **Emergency schedules** F-E, _S-E
The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	17/22

Section 14. Transport information

IATA	: The environmentally hazardous substance mark may appear if required by other transportation regulations.
Special precautions for user	: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	: Not available.

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 5(a)2 final significant new use rules: No products found. TSCA 5(e) substance consent order: No products found. TSCA 8(a) PAIR: 2-methoxy-1-methylethyl acetate; naphthalene TSCA 8(a) CDR Exempt/Partial exemption: Not determined TSCA 12(b) annual export notification: strontium chromate United States inventory (TSCA 8b): All components are active or exempted. Clean Water Act (CWA) 307: strontium chromate; toluene; barium chromate; naphthalene Clean Water Act (CWA) 311: strontium chromate; toluene; isobutyl acetate; naphthalene
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
SARA 302/304	
Composition/information on ingredients	No products were found.
SARA 304 RQ	: Not applicable.
SARA 311/312	
Classification	: FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Section 15. Regulatory information

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Composition/information on ingredients

Name	%	Classification
strontium chromate	≥10 - <20	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 2 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 2 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 FLAMMABLE LIQUIDS - Category 3
2-methoxy-1-methylethyl acetate	≥10 - ≤25	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
butanone	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A
toluene	≥10 - ≤25	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
isobutyl acetate	≤10	ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
titanium dioxide barium chromate	≤3 <1	CARCINOGENICITY - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 2 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1B CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
propylidynetrimethanol Solvent naphtha (petroleum), heavy arom. Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines	≤1 ≤0.3 ≤0.3	TOXIC TO REPRODUCTION - Category 2 CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1 SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
crystalline silica, respirable powder	≤0.3	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	19/22

Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	strontium chromate toluene barium chromate	7789-06-2 108-88-3 10294-40-3	≥10 - <20 ≥10 - ≤25 <1
Supplier notification	strontium chromate toluene barium chromate	7789-06-2 108-88-3 10294-40-3	≥10 - <20 ≥10 - ≤25 <1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: STRONTIUM CHROMATE; KAOLIN DUST; METHYL ETHYL KETONE; TOLUENE; ISOBUTYL ACETATE; TITANIUM DIOXIDE; PRECIPITATED SILICA
New York	: The following components are listed: Strontium chromate; Methyl ethyl ketone; Toluene; iso-Butyl acetate
New Jersey	: The following components are listed: STRONTIUM CHROMATE; KAOLIN; METHYL ETHYL KETONE; TOLUENE; ISOBUTYL ACETATE; TITANIUM DIOXIDE; SILICA, AMORPHOUS, PRECIPITATE & GEL; BARIUM CHROMATE; SILICA, QUARTZ
Pennsylvania	: The following components are listed: CHROMIC ACID (H ₂ CRO ₄), STRONTIUM SALT (1:1); KAOLIN; 2-BUTANONE; BENZENE, METHYL-; ACETIC ACID, 2-METHYLPROPYL ESTER; TITANIUM OXIDE; PRECIPITATED SILICA

California Prop. 65

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
strontium chromate	Yes.	Yes.	Cancer, Developmental, Reproductive female, Reproductive male
toluene	-	Yes.	Developmental
titanium dioxide	-	-	Cancer
barium chromate	Yes.	Yes.	Cancer, Developmental, Reproductive female, Reproductive male
crystalline silica, respirable powder	-	-	Cancer
2,2'-iminodiethanol	-	-	Cancer
naphthalene	Yes.	-	Cancer

Inventory list

Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.

Section 15. Regulatory information

New Zealand	: All components are listed or exempted.
Philippines	: At least one component is not listed.
Republic of Korea	: All components are listed or exempted.
Taiwan	: At least one component is not listed.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
RESPIRATORY SENSITIZATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
GERM CELL MUTAGENICITY - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

History

Date of printing	: 2/11/2026
Date of issue/ Date of revision	: 10/14/2025
Date of previous issue	: 8/28/2025
Version	: 4

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	21/22

Section 16. Other information

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

 Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws. Any person using this product must determine for themselves, by preliminary tests or otherwise, the suitability of this product for their purposes. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. The application, use and processing of AkzoNobel's products and the products manufactured by Buyer on the basis of AkzoNobel's technical advice are beyond AkzoNobel's control and, therefore, entirely Buyer's own responsibility. AkzoNobel makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

IA_413

Date of issue/Date of revision	: 10/14/2025	Version : 4
Date of previous issue	: 8/28/2025	22/22